

KCSC-4BR3

4MP 3.6mm Fixed Lens IR Bullet Camera

4MP

2MP

3.6
mm

QHD

WDR

DC12V

Features

- 1/2.8" 5.14 Mega SONY CMOS Sensor
- 3.6mm Fixed Lens
- QHD (2560x1440) , FHD (1920x1080)
- Smart IR & WDR
- DAY&NIGHT
- IP67
- Long-range, less heat (4 x Hi-power Chip leds)
- 12V DC Input
- External Change Video output
(HD - SDI / EX 1.0 / EX 2.0 / AHD / TVI / 960H)
- Made in Korea



Specifications

KCSC-4BR3	
CAMERA	
Image Sensor	1/2.8" 5Mega CMOS Sensor
Total Pixels	2704 (H) × 2104 (V)
Effective	2616 (H) × 1964 (V)
Resolution	2560 x 1440 Pixels
S/N Ratio	More than 40dB (AGC off)
Frame	30fps QHD
OSD	English/Chinese/Chinese(S)/Japanese/Korea
Day & Night	Auto/Color/B&W/EXTERN
ATW	1800 ~ 10500K
High Speed Shutter	1/30(1/25) ~ 1/30Ksec
WDR	Line mode(30fps)/ Frame mode(15fps) and ROI
D-WDR	Off / On
BLC	Off / On (Size, Position)
HLC	Level Setting(0~20), Color
AGC	Level Setting(0~10) : Max 72dB(TBD)
White Balance	AUTO / AUTO ext / PUSH / MANUAL
DNR	2D+3DNR, OFF/LOW/MIDDLE/HIGH
Motion Detection	Off / On
Privacy Mask	BOX(16 Areas), Polygon(8 Areas)(On/Off, Color, Position)
Sens-Up	x2,x4,x8,x16,x32
De-Fog	2AUTO/Manual
Shapness, Reverse (H,V)	0~10, Mirror, Flip
In / Output	Alarm Output, Ext IR Mode, IR LED Off/On
Analog Video Output	Analog VBS 1.0Vp-p (75ohm Terminated)
HD Analog Video Output	TVI VBS 1.0Vp-p (75ohm Terminated)
	AHD VBS 1.0Vp-p (75ohm Terminated)
Digital Serial Video Output	Selectable HD-SDI or EX-SDI1.0/2.0/2.1(Long Reach)

GENERAL

Power Input	DC 12V ±10%
	Less than 400mA
Operation Temperature	-10°C ~ +50°C
Dimensions	210mm (D) × 69mm (ø)
Weight	620g

Dimensions

